

WPH Series High Temperature Flow Monitor



Nuffield Road,
St. Ives, Cambs.,
PE27 3LZ, UK

Tel: +44(0)1480 397400

Fax: +44(0)1480 466555

www.webtec.co.uk

E-mail: sales@webtec.co.uk

Up to

- 550 lpm, 150 US gpm
- 420 bar, 6000 psi

The WPH series high temperature in-line flow monitors are designed for continuous monitoring or intermittent use on high temperature fluid systems up to 204°C (not suitable for steam).

The tubular scale is easily read through the clear Pyrex window and ensures checks can be made to determine pump performance and setting of flow control valves. Wetted seals are Viton®. The flow monitors are available in a choice of three different materials, aluminium, brass or stainless steel to suit your application.

The WPH series flow monitors do not require straight inlet or outlet piping and can be installed in any orientation. The advanced design of the sharp edged orifice ensures good reliability over a wide viscosity range and minimises the effect of contamination. Accuracy is 2.5% over the centre third of the scale and 4% over the entire flow range.



Features

- Suitable for temperatures up to 204° C (400° F)
- Wide variety of flow ranges
- Pressure rating up to 420 bar (6000 psi)
- Port sizes from 3/8" to 2"
- Direct reading dual calibration, lpm & US gpm
- Accurate within 2.5% over mid-scale, 4% FSD
- Advanced stainless steel sharp edge orifice
- Unrestricted mounting in any orientation

Manufacturers of hydraulic components and test equipment
for the Mobile, Industrial and Agricultural industries



WPH-BU-ENG-1939.pdf 09/11
(Issue 3)

Specifications

Measuring accuracy

± 2.5% of full-scale in the centre third of the measuring range
± 4% of full-scale over the entire scale range

Repeatability

± 1% of full scale

Maximum operating pressure

Aluminium & brass monitors 240 bar (3000 psi),
stainless steel 420 bar (6000 psi)

(Note: See temperature / pressure de-rating chart)

Maximum operating temperature

204° C (400° F)

315° C (600° F model available)


Pressure differential

See graphs below

Standard calibration fluids


DTE 25 @ 43°C, 0.873 sg.

Temperature De-rating for Aluminium & Brass Monitors




Pressure differential graphs categorised by size code


Series 3 (3/8" - 1/2")



Series 4 (3/4" - 1")



Series 5 (1 1/4" - 2")



-15 = Model number (see Sales Brochure)

14.5 psi = 1 bar, 1 US gpm = 3.785 lpm

Construction

Wetted components:

High pressure casing, end ports and tapered shafts *Aluminium, Brass & Stainless Steel*

Seals: *Viton®*

Transfer magnet *Teflon® coated Alnico*

Floating Orifice disc: *Stainless Steel*

All other internal parts *Stainless Steel*

Non-wetted components:



Window tube: *Pyrex*

Window seals: *Teflon®*

(Teflon® is a registered trademark of DuPont)
(Viton® & Kalrez® are registered trademarks of Dow DuPont Elastomers)

Dimensions

Size code	3	4	5	5 (2" ports)
Dim. A mm (inches)	48 (1.9)	60 (2.4)	90 (3.5)	90 (3.50)
Dim. B mm (inches)	167 (6.6)	182 (7.2)	258 (10.2)	322 (12.7)



Product Selector

Standard Flow Meter Part Number
(For custom units, consult the Sales Office)

Series # WP ☐ ☐ ☐ - ☐ ☐ ☐ - ☐ ☐ Webtec Part Number

Step 1 - Style

BASIC in line for liquid	= B
Pneumatic for air and gas	= G
High Temp 200 °C (400 °F)	= H
Flow alarm, 1 switch	= M
Flow alarm, 2 switches	= N
Flow transmitter	= R
Phosphate esters	= P

Step 2 - Port / Line Size

1/4" - 1/2"	= 3
3/4" - 1"	= 4
1 1/4" - 2"	= 5

Step 3 - Material

Aluminium	= A
Brass	= B
Stainless Steel	= S

Step 4 - Pressure rating maximum

42 bar (600 psi)	= 4
(Air and gas / Aluminium and brass)	
69 bar (1000 psi)	= 5
(Air and gas / Stainless steel)	
240 bar (3500 psi)	= 6
(Liquids / Aluminium and brass)	
420 bar (6000 psi)	= 7
(Liquids / Stainless steel)	

Step 5 - Fluid:

Air and Gases	= A
Oil and 0.873 specific gravity	= H
Water and 1.0 specific gravity	= W

Step 6 - Thread porting

Size 3 available threads

1/4" NPTF	= S
1/8" NPTF	= A
1/2" NPTF	= B
9/16" -18UN #6 SAE ORB	= E
3/4" -16UN #8 SAE ORB	= F
7/8" -14UN #10 SAE ORB	= G
3/8" BSPP	= R
1/2" BSPP	= T

Size 4 available threads

3/4" NPTF	= C
1" NPTF	= D
1-1/16" -12UN #12 SAE ORB	= H
1-5/16" -12UN #16 SAE ORB	= J
3/4" BSPP	= U
1" BSPP	= V

Size 5 available threads

1-1/4" NPTF	= K
1-1/2" NPTF	= L
2" NPTF	= M
1-5/8" -12UN #20 SAE ORB	= N
1-7/8" -12UN #24 SAE ORB	= P
2" -12UN #32 SAE ORB	= Q
1-1/4" BSPP	= W
1-1/2" BSPP	= Y
2" BSPP	= X

Please note - SAE porting not available in brass

Step 7 - Flow ranges

Oil and Water LPM (USgpm)	@100 PSIG SCFM		Size
0.5-4 (0.05 - 1)	1.5 -12	= 01	3 only
0.5-4 (0.1 - 1) water			
1-8 (0.2-2)	4-23	= 02	3 & 4
2-19 (0.5-5)	5-50	= 05	3 & 4
4-38 (1-10)	10-100	= 10	3 & 4
4-56 (1-15)	25-150	= 15	3 & 4
10-75 (2-20)	20-215	= 20	4 only
10-100 (2-25)	20-250	= 25	4 & 5
10-115 (3-30)	30-330	= 30	4 only
15-150 (4-40)	30-400	= 40	4 only
15-190 (5-50)	40-500	= 50	4 only
15-190 (5-50)	30-470	= 50	5 only
30-280 (8-75)	30-750	= 75	5 only
40-375 (10-100)	150-900	= 88	5 only
75-550 (20-150)	150-1300	= 99	5 only

Step 8 - Optional flow directions

Uni-directional	=
Bi directional	= BI
Reverse flow	= RF

Not all flow ranges are available with Bi and reverse directional options, please consult the sales office.

Case Drain Monitor

Series # WPC ☐ ☐ ☐ - ☐ ☐ ☐ - ☐ ☐ Webtec Part Number

Port / Line Size

1/2"	= 3
3/4" - 1"	= 4

Material

Aluminium	= A
-----------	-----

Pressure Rating Max.

70 bar (1000 psi)	= 5
-------------------	-----

Fluid Media

Oil and 0.873 specific gravity	= H
Water and 1.0 specific gravity	= W

Flow ranges (oil and water)

LPM (USgpm)		Size
0.5-4 (0.05 - 1)	= 01	3 only
0.5-4 (0.1 - 1) water		
1-8 (0.2-2)	= 02	3 & 4
2-19 (0.5-5)	= 05	3 & 4
4-38 (1-10)	= 10	3 & 4
4-56 (1-15)	= 15	3 & 4
10-75 (2-20)	= 20	4 only
10-100 (2-25)	= 25	4 & 5
10-115 (3-30)	= 30	4 only

Thread Type

Porting (All Female)		Size
1/2" BSPP	= T	3 only
3/4" BSPP	= U	4 only
1" BSPP	= V	4 only
1/2" NPTF, dry seal	= B	3 only
3/4" NPTF, dry seal	= C	4 only
1" NPTF, dry seal	= D	4 only