

# ÇELİK ÇEKME BORULAR

## HİDROLİK ÇELİK ÇEKME HAT BORUSU / DIN 2391 NBK ST 37,4-GALVANİZ KAPLI

Dış Çap	Et Kalınlığı	Ağırlık	Çalışma Basıncı
mm	mm	kg/m	bar
Ø6	1,0	0,123	392
Ø8	1,0	0,173	294
Ø10	1,5	0,314	374
Ø12	1,5	0,388	311
Ø12	2,0	0,495	415
Ø14	1,5	0,449	267
Ø15	1,5	0,499	249
Ø15	2,5	0,771	450
Ø16	2,0	0,690	311
Ø16	2,5	0,832	389
Ø18	1,5	0,610	207
Ø18	2,0	0,789	277
Ø18	3,0	1,110	450
Ø20	2,0	0,888	249
Ø20	2,5	1,079	311
Ø22	2,0	0,986	226
Ø25	2,0	1,134	200
Ø25	2,5	1,387	249
Ø25	3,0	1,628	299
Ø25	4,0	2,072	400
Ø28	3,0	1,850	267
Ø30	3,0	1,997	249
Ø30	4,0	2,565	332
Ø35	3,0	2,367	213
Ø35	4,0	3,058	285
Ø38	4,0	3,354	262
Ø38	5,0	4,066	328
Ø42	3,0	2,885	178
Ø42	4,0	3,748	237

